

Cavity Varnish w/ Fluoride

Page 1 of 6

Section 1 – Identification

Product Name: Cavity Varnish w/ Stannous

Fluoride

Active Ingredient: Potassium Fluoride & Stannous

Fluoride

Manufacturer: Dharma Research, Inc.

5220 N.W. 72nd Avenue Miami, FL 33166

Information Contacts: (305) 482-9669 **Toll Free:** 1-877-833-3725

Emergency Phone Numbers: US & Canada 1 (877) 833-3725

Family: Medicaments (Desensitizer)
Product Use: Professional Dental Varnish

Product #: 14-00015

Section 2 – Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- Extremely Flammable keep container closed and avoid static discharge
- Vapors may cause drowsiness or dizziness.
- Toxic if large quantities are swallowed or inhaled.
- Potentially irritating to eyes and respiratory system
- Please read entire SDS for additional information.



Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Inhalation, skin, and ingestion.

Eye Splashes or close proximity to vapors may cause redness of the eye.

Skin Repeated/prolonged contact may cause dryness or cracking of the skin. Possible irritation will take

place.

Ingestion Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing

large amounts may be harmful. Symptoms include irritation of the throat, nausea, dizziness, and upset

stomach, possibly organ (liver) damage.

Inhalation Inhaling vapors may cause drowsiness or dizziness. Irritation to respiratory tract may occur if prolong

exposure to vapors take place.

NOTE: Refer to Section 11, Toxicological Information for Details

Section 3 – Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure OSHA	Limits ACGIH	Carcinogen	%
	- 100			TWA/STEL	TWA/STEL	IARC/NTP/OSHA	
Ethanol	64-17-5	200-578-6	Alcohol	TWA = 1000 ppm or	TWA = 1880 mg/	No/No/Yes	50-75
				1900 mg/ m^3	m^3		
Ethyl Ether	60-29-7	200-467-2	Ethyl Ether	TWA = 400 ppm or	TWA = 400 ppm	Not Listed	13-30
				1200 mg/ m^3	STEL = 500 ppm		
Potassium	7789-23-3	232-151-5	Potassium	$TWA = 2.5 \text{ mg/ m}^3$	TWA = 2.5 mg/	Not Listed	0-3
Fluoride			Fluoride		m^3		
Stannous	7783-47-3	231-999-3	Stannous	$TWA = 2.5 \text{ mg/ m}^3$	TWA = 2.5 mg/	Not Listed	0-3
Fluoride			Fluoride	_	m^3		

 $\begin{array}{ll} N\!\!\!/E - None \ Established & N\!\!\!/DA - No \ Data \\ N\!\!\!/R - Not \ Reviewed & Available \\ & N\!\!\!/A - Not \ Applicable \end{array}$

(items in parenthesis relate to 1999/45/EC)

Ethanol: Danger Symbol – GHS02 (F)

Hazard Statement – H225 (R11)

Precautionary Statement – P102 (S1/2), P404 (S7), P210 (S16)

Ethyl Ether: Danger Symbol – GHS02 (F), GHS07 (Xn) Hazard Statement – H224 (R12), EUH019 (R19), H302 (R22), EUH066 (R66), H336 (R67)



Cavity Varnish w/ Fluoride

Page 2 of 6

Precautionary Statement – P102 (S2), P403 (S9), P210 (S16), P280 (S36/37/39), P273 (S29), P243 (S33)

Potassium Fluoride: Danger Symbol – GHS06 (T) Hazard Statement – H331 + H311 + H301 (R23/24/25) Precautionary Statement – P102

(S1/2), P305+334 (S26), P309+314 (S45)

Stannous Fluoride: Danger Symbol – GHS05 (C), GHS07 (Xn) Hazard Statement – H302 (R22), H313 (N/A), H315 (R38), H318 (R41)

Precautionary Statements – P280 (S36/37/39), P305+351+338 (S26)

See Section 16 for Hazard and Precautionary Statement Key.

Section 4 – First Aid Measures

First Aid for Eye Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.

First Aid for Skin Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort

persists.

First Aid for Ingestion If greater than normal dose is swallowed, do not induce vomiting. Drink large quantity of water or

milk. Seek medical attention.

First Aid for Inhalation Move to fresh air. Seek medical attention if discomfort persists.

Section 5 – Fire Fighting Measures

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
Around 50 °F / 10 °C	N/A	Around 685 °F / 363 °C

Method:

Extinguishing Media: "Alcohol" foam, Carbon dioxide, dry chemical foam

Fire Fighting For large fires, apply water from as far as possible. Use very large quantities of water applied as a mist

Instructions: or spray, solid streams of water may be ineffective. Cool all affected containers with water.

Unusual Hazards: N/A

Section 6 – Accidental Release Measures

Spill or Release Procedures Minor spills - Clean up immediately, avoid contact with skin and eyes. Wipe area and clean with soapy water

Major spills – Clear area of personnel. Restrict access to area. Eliminate ALL ignition sources. Avoid contact with skin and eyes. Use non-sparking tools. Absorb spill with inert material, such as sand, dry lime, or soda ash, and dispose of

properly.

See section 8 & section 12.

Section 7 – Handling and Storage

Handling Limit all unnecessary personal contact. Stay away from ignition sources and open flames. Avoid breathing

vapors. Wear appropriate PPE.

Storage Store in a cool, well ventilated area away from heat, sparks and flame. Keep containers closed when

not in use. Keep in original container provided by manufacturer.

Explosion Hazard None.

Section 8 – Exposure Controls / Personal Protection

Engineering Mechanical exhaust is HIGHLY recommended. Safety show, eye bath, and fire equipment (spill response)

Controls should be accessible.

Personal Protective Equipment

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a

hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard

EN166 be conducted before using this product.

Eye/ Face Chemical safety glasses / goggles or splash shields are required when handling. Ensure eye bath is on hand.

Protection

Skin Protection Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole

body suit.

Respiratory In case of insufficient ventilation, wear suitable respiratory equipment with correct respiratory cartridge. If the

Protection respirator is the sole means of protection, use a full face supplied air respirator.



Cavity Varnish w/ Fluoride

Page 3 of 6

Section 9 – Physical and Chemical Properties

Appeara	nce	Odor & O	Odor Threshold	PН	Spec	ific Gravity	Viscosity	% V	olatile
Colored Liquid N/A		N/A	N/A	(H2	O = 1): N/A	N/A	N	I/A	
		. 1	A . 1077					1	
Boiling Point/ Freezing Point	Decomposit Temperatu		Octanol/Water rtitioning Coefficion		apor ssure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water
			Log Po/w						(20°C)
N/A	N/DA		N/DA	1	V/A	N/A	N/A	N/A	N/A

Flash Point (°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
N/A	N/A	N/A

Section 10 – Stability and Reactivity

Stability: Incompatibility (Materials to Avoid):

Stable Oxidizing agents, peroxides, alkali metals, ammonia.

Hazardous Decomposition Products: Hazardous Polymerization:

Carbon dioxide and monoxide Will not occur

Conditions to Avoid: Heat and incompatible materials

Section 11 – Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation – skin	Irritation – Eye
N/DA	N/DA	N/DA	N/DA	N/ DA

Sensitization	Mutagenicity	Sub-chronic Toxicity
N/ DA	N/DA	N/ DA

Section 12 – Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA	N/ DA	N/ DA	N/ DA	N/ DA

Chemical Fate Information

Biodegradability	N/DA. This material is not expected to significantly bio-accumulate.
Chemical Oxygen Demand	N/ DA

Section 13 – Disposal Considerations

Dispose of in compliance with governmental regulation (state and federal).

Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.

Section 14 – Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	UN1170, Ethanol Solution, 3, II
Identification Number:	1170
Marine Pollutant:	No
Special Provisions:	24, IB2, T4, TP1



Cavity Varnish w/ Fluoride

Page 4 of 6

Emergency Response Guidebook (ERG) #:	127
IATA (DGR):	
Proper Shipping Name:	UN1170, Ethanol Solution (Ethyl Alcohol Solution), 3, II
Class or Division:	3
UN or ID Number:	1170
Packaging Instructions:	II
Emergency Response Guidance (ICAO)#:	N/A
IMO (IMDG):	
Proper Shipping Name:	UN1170, Ethanol Solution (Ethyl Alcohol Solution), 3, II
Class or Division:	3
UN or ID Number:	1170
Special Provisions & Stowage/Segregation:	
Emergency Schedule (EmS)#:	N/A
Other Information:	Qualifies for ORM-D consumer commodity packaging exemptions.

Section 15 – Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	This product contains the following HAP's or ODS: • NONE
Clean Water Act: Priority Pollutant	This product contains the following chemicals listed under the U. S. Clean Water Act
Ponutant	Priority Pollutant and Hazardous Substance List: None
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food-packaging additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. It's hazards are:
	• Ethanol – CAS #64-17-5 (Flammable)
	• Ethyl Ether – CAS #60-29-7 (Flammable)
	• Potassium Fluoride – CAS #7789-23-3 (Health hazard)
D CD 1	Stannous Fluoride – CAS #7783-47-3 (Toxic, Irritant) This is a second of the sec
RCRA	This product contains the following chemicals considered to be hazardous waste under RCRA (40 CFR 261).
	• None
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA Title III: Section 302	This product does contain chemicals regulated under Section 304 as extremely hazardous
(TPQ)	chemicals for emergency release notification ("CERCLA" List).
	• Ethyl Ether – CAS #60-29-7 (100 lb final RQ)
SARA Title III: Section 311-312:	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). It's hazards are:
	Ethanol – CAS #64-17-5 (Immediate Health Hazard, Fire Hazard, Chronic Health Hazard)
	Ethyl Ether – CAS #60-29-7 (Fire Hazard, Acute Health Hazard, Chronic Health Hazard)
	Potassium Fluoride – CAS #7789-23-3 (Immediate Hazard)
	• Stannous Fluoride – CAS #7783-47-3 (Acute & Chronic Health Hazard)
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting
	requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
	• None
TSCA Section 8(b): Inventory:	This product does contain chemicals listed on the TSCA inventory or otherwise complies with TSCA pre-manufacture notification requirements.
	• Ethanol – CAS # 64-17-5
	• Ethyl Ether – CAS #60-29-7



Cavity Varnish w/ Fluoride

Page 5 of 6

	Potassium Fluoride – CAS #7789-23-3
TSCA Significant New Use Rule:	• Stannous Fluoride – CAS #7783-47-3
	None of the chemicals in this material have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:	Ethyl Ether – CAS #60-29-7
California No Significant Risk	Potassium Fluoride – CAS #7789-23-3
Rule:	
MA Right-to-Know Law:	Ethanol – CAS # 64-17-5
	Ethyl Ether – CAS #60-29-7
NJ Right-to-Know Law:	Ethanol – CAS # 64-17-5
	Ethyl Ether – CAS #60-29-7
	Potassium Fluoride – CAS #7789-23-3
	Stannous Fluoride – CAS #7783-47-3
PA Right-to-Know Law:	Ethanol – CAS # 64-17-5
	Ethyl Ether – CAS #60-29-7
	Potassium Fluoride – CAS #7789-23-3
	Stannous Fluoride – CAS #7783-47-3
FL Right-to-Know Law:	N/A
MN Right-to-Know Law:	Ethyl Ether – CAS #60-29-7
	Potassium Fluoride – CAS #7789-23-3


International Regulations

CDSL: Canadian Inventory	Ethanol – CAS # 64-17-5
(on Canadian Transitional List)	Ethyl Ether – CAS #60-29-7
(Potassium Fluoride – CAS #7789-23-3
	Stannous Fluoride – CAS #7783-47-3

Labeling according to EC directives - 1272/2008 (CLP) AND 1999/45/EC (items in parenthesis relate to 1999/45/EC)

European Community:





- DANGER SYMBOLS: **GHS07** (**Xn**) Harmful / Acute Toxicity. **GHS02** (**F**) Flammable. **GHS08** (**n**/**a**) Health hazard (Organ Toxicity)
- HAZARD STATEMENT: **H225** (**R11**). **H302** (**R22**). **H312** (**R21**). **H320** (**N/A**). **H332** (**R20**). **H371** (**R68/22**).
- PRECAUTIONARY STATEMENT: P102 (S2). P210 (S15). P261 (S24). P280 (S36/37/39). P305+334 (S26). P309+314 (S45). P404 (S7). P403 (S9). P243 (S33).

Section 16 – Other Information

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

(items in parenthesis relate to 1999/45/EC)

Danger Symbols:

 $GHS02\ (F)-Highly\ Flammable.\ GHS07\ (Xn)-Harmful.\ GHS06\ (T)-Toxic.\ GHS06\ (C)-Corrosive$


Hazard Statement: H224 (R12), Extremely flammable liquid and vapor. H225 (R11), Highly flammable liquids and vapors. EUH019 (R19), May form explosive peroxides. H302 (R22), Harmful if swallowed. EUH066 (R66), Repeated exposure may cause skin dryness or cracking. H336 (R67), May cause drowsiness or dizziness. H331 + H311 + H301 (R23/24/25), Toxic if inhaled or in contact with skin or swallowed. H312 (R21), Harmful in contact with skin. H320 (N/A), Causes eye irritation. H332 (R20), Harmful if inhaled. H371 (R68/22), May cause damage to organs. H313 (N/A), Maybe harmful in contact with skin. H315 (R38), Causes skin irritation. H318 (R41), Causes serious eye damage.

Precautionary Statement: P102 (S1 or S2), Keep out of reach of children. P210 (S15 or S16), Keep away from heat/sparks/open flames/hot surfaces. P273 (S29), Avoid release into environment. P243 (S33), Take precautionary measures against static discharge. P280 (S36/37/39), Wear protective gloves/clothing/eye protection/face protection. P305+334 (S26), In case of contact with eyes, rinse immediately with water. P309+314 (S45), If exposed or you feel unwell, get medical advice/attention. P404 (S7), Store in a closed container. P403 (S9), Store in a well ventilated place. P261 (S24), Avoid breathing dust/fume/gas/mist/vapors. P305+351+338 (S26), If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.



Cavity Varnish w/ Fluoride

Page 6 of 6



SDS Prepared by:	Ricardo Carles
Revision History:	02/12/11 Revision A

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable.

Dharma components are provided on an as is basis without warranties of any kind either expressed or implied. Dharma does not warrant the use or the results of use of the materials sold on an as is basis since they are intended for remanufacturing or repackaging. It is the sole responsibility of the user to examine and determine appropriate application and regulatory requirements associated with said Dharma components.